



Requirements:

- Corrosion test according to: DIN EN 15338
- Slides tested according to: DIN EN 15338 Level 2
- Use pan head screws 4mm x 16mm (two per plate)*
- or metrical thread screws diameter 6mm (one per plate) **
- to attach the slide to the cabinet

Min. cabinet depth: 753 mm
 Loading capacity (DIN EN 15338): 100 kg/GN
 In application with add.
 wheel support load capacity: 130 kg/GN

screw position

- * pan head 4mm
- ** metrical thread screw 6mm

The reproduction, distribution and utilization of this drawing as well as the communication of its contents to others without explicit authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.							
Mass:	0,00	g	measures to be checked and control numbers according to HS 5000	Date	Name	Ind.	VS
Volume:	0,00	cm ³		04.08.14	Beckend.	1	0
Surface:		cm ²	ISO 16016	10.01.11	TPeterka	0	0
 Paul Hettich GmbH & Co. KG	Spec. applicable	DIN A3	Date	Name	requirements for the corrosion resistance according to HS 150		
	Maturity Level:	Detailer	10.01.11	TPeterka	Level:		
	General tolerance according to	Approv.	12.12.14	Heckel	Description		
	In case of change check	Scale	Proj.	State	Big Duplex 750mm/ 684mm		
	1:2			RELEASED	Type	Drawing group	Drawing No.
					Cust	from	to
					0	QZ 10049	0000 01 00
						QZ 10049	0000 01 00
					Develop.-No.	Index	Vers.
					X 200072 1221 00 00	01	00
						1	00
						1	00